

## TECHNICAL DATA

Model: 4000

Item	Specification	Unit
Power supply	AC 100V 50/60Hz	
Power consumption	100W	
Rated current	0.5A	
Rated voltage	100V	
Rated power	100W	
Rated frequency	50/60Hz	
Rated speed	1500rpm	
Rated torque	0.15Nm	
Rated efficiency	85%	
Rated power factor	0.85	
Rated insulation class	F	
Rated protection class	IP40	
Rated ambient temperature	0~40°C	
Rated altitude	1000m	
Rated humidity	5~95%RH	
Rated vibration	0.5mm/s	
Rated shock	10G	
Rated life	20000h	
Rated speed accuracy	±1%	
Rated torque accuracy	±1%	
Rated efficiency accuracy	±1%	
Rated power factor accuracy	±1%	
Rated insulation class	F	
Rated protection class	IP40	
Rated ambient temperature	0~40°C	
Rated altitude	1000m	
Rated humidity	5~95%RH	
Rated vibration	0.5mm/s	
Rated shock	10G	
Rated life	20000h	
Rated speed accuracy	±1%	
Rated torque accuracy	±1%	
Rated efficiency accuracy	±1%	
Rated power factor accuracy	±1%	

Technical data is subject to change without notice. Please refer to the latest version of the technical data. The technical data is for reference only. The actual performance may vary due to the manufacturing process and the operating conditions. The technical data is for reference only. The actual performance may vary due to the manufacturing process and the operating conditions.